

Standard tube elements 430

400^{series}

Watson-Marlow Pumps


FEATURES AND BENEFITS

- Standard range of elements with polypropylene fittings
- Use of tube elements secure optimal tube handling by the pump
- The elements are optimal fitted to the design of each pump type
- Optional tubing and fitting materials are available on request



Watson-Marlow...Innovation in Full Flow

DIMENSIONS



(one element per channel)

ORDER INFORMATION

Standard 430 elements for 400F/D2 and 400F/D3 pumpheads			
Bore/Wall	Bioprene	Peroxide cured Silicone	Connects to
0.5/1.0mm	049.EF6D.N05	-	Tube bore 3,0
1.0/1.0mm	049.EF6D.N10	049.EH6D.N10	Tube bore 3,0
2.0/1.0mm	049.EF6D.N20	049.EH6D.N20	Tube bore 3,0
3.0/1.0mm	-	049.EH6D.N30	Tube bore 3,0

All flow rates shown were obtained pumping water at 20°C (68°F) with zero suction and delivery heads. Watson-Marlow, Bioprene and Marprene are trademarks of Watson-Marlow Limited. Disclaimer: The information contained in this document is believed to be correct but Watson-Marlow Limited accepts no liability for any errors it contains, and reserves the right to alter specifications without notice. LoadSure is a trademark of Watson-Marlow Limited. © STA-PURE PFL and © STA-PURE PCS are registered trademarks of W.L. Gore & Associates Inc. Please state the product code when ordering pumps and tubing.

**WATSON
MARLOW**
Pumps

wmpg.com
info@wmpg.com
+44 (0) 1326 370370